

## 5+5MP Outdoor Wi-Fi Dual-Lens Pan & Tilt Camera

# DH-P5D-5F-PV



### Series Overview

The Picoo Dual Series, which is under the Dahua Wireless series, consists of cameras equipped with both fixed lens and PT lens. This unique combination allows for simultaneous live monitoring of two areas, providing coverage from multiple angles. Leveraging its dual lenses, the camera performs smart detection using advanced functions like AI human and vehicle detection, effectively minimizing false alarms. Additionally, with the assistance of the PT lens, the camera has the capability to automatically track moving targets. The camera also triggers sound and light alarms upon detecting an intrusion, promptly sending notifications to the mobile client to ensure you remain up to date regardless of your location. These cameras are widely utilized in small-scale scenes such as shops and restaurants.

 <b>Dual 3K</b> Clear images with sharp details	 <b>Dual-lens, Double Vision</b> One camera, double the protection	 <b>Linkage Tracking (2.8mm+6mm only)</b> Coordinated fixed lens and PT lens monitoring ensures complete vigilance in security
 <b>Dual Channel Smart Detection</b> Smart detection for both lenses to focus on what matters	 <b>AI Human Detection</b> Focuses on what matters and reduces false alarms	 <b>AI Vehicle Detection</b> Focuses on what matters and reduces false alarms
 <b>Tap and View (2.8mm+6mm only)</b> Tap anywhere on the close-up view in the App, and the PT lens will	 <b>IP66 Protection</b> Withstands harsh environments	 <b>Auto Tracking</b> Automatic tracking of targets
 <b>Sound and Light Alarm</b> Provides instant alarms to deter intruders	 <b>Smart Dual Light</b> Captures color details for post-event review	 <b>Micro SD Card</b> Low-cost storage
 <b>Bluetooth Pairing</b> Fast pairing with Bluetooth	 <b>Wi-Fi 6</b> The perfect integration of speed and anti-interference	 <b>H.265</b> Advanced H.265 Compression Technology



### Upgrade Your Experience with DMSS

Dahua Mobile Security Surveillance (DMSS) is a professional remote surveillance management platform that offers remote monitoring, device migration, and sharing. When connected to the internet, the platform provides real-time alerts to improve surveillance efficiency and grant flexibility in security management.





## Specifications

### Camera (2.8 mm+6 mm)

#### Fixed Lens

Image Sensor	1/3" CMOS
Max. Resolution	2880 (H) × 1620 (V)
Illumination Distance	Up to 30 m (98.43 ft) (IR) Up to 20 m (65.62 ft) (Warm light)
Illuminator Number	2 (IR LED); 2 (Warm light)
Angle Adjustment	-10° to 15°
Lens Type	Fixed-focal
Focal Length	2.8 mm
Max. Aperture	F1.6
Field of View	H: 95°; V: 53°; D: 110°

#### PT Lens

Image Sensor	1/3" CMOS
Max. Resolution	2880 (H) × 1620 (V)
Illumination Distance	Up to 50 m (164.04 ft) (IR) Up to 40 m (131.23 ft) (Warm light)
Illuminator Number	2 (IR LED); 2 (Warm light)
Angle Adjustment	Pan: 0° to 352°; Tilt: 0° to 90°
Lens Type	Fixed-focal
Focal Length	6 mm
Max. Aperture	F1.6
Field of View	H: 49°; V: 26°; D: 57°

### Camera (3.6 mm+3.6 mm)

#### Fixed Lens

Image Sensor	1/3" CMOS
Max. Resolution	2880 (H) × 1620 (V)
Illumination Distance	Up to 30 m (98.43 ft) (IR) Up to 30 m (98.43 ft) (Warm light)
Illuminator Number	2 (IR LED); 2 (Warm light)
Angle Adjustment	-10° to 15°
Lens Type	Fixed-focal
Focal Length	3.6mm
Max. Aperture	F1.6
Field of View	H: 78°; V: 42°; D: 92°

#### PT Lens

Image Sensor	1/3" CMOS
Max. Resolution	2880 (H) × 1620 (V)
Illumination Distance	Up to 30 m (98.43 ft) (IR) Up to 30 m (98.43 ft) (Warm light)
Illuminator Number	2 (IR LED); 2 (Warm light)
Angle Adjustment	Pan: 0° to 352°; Tilt: 0° to 90°
Lens Type	Fixed-focal
Focal Length	3.6mm
Max. Aperture	F1.6
Field of View	H: 78°; V: 42°; D: 92°

## Intelligence

Human Detection	Yes
Vehicle Detection	Yes
<b>Audio and Video</b>	
Video Compression	H.265
Video Frame Rate	Main stream: 2880 × 1620@15 fps sub stream: 640 × 360@15 fps *The values above are the max. frame rates of each stream; for multiple streams, the values will be subjected to the total encoding capacity.
Video Bit Rate	H.265: 768 kbps–4096 kbps
Day/Night	Auto(ICR)/Color/B/W
WDR	DWDR
Motion Detection	Yes
Image Rotation	0°/180°
Built-in MIC	Yes, built-in Mic
Built-in Speaker	Yes, built-in speaker
Audio Compression	G.711a

## Network

Network Port	RJ-45 (10/100 Base-T)
Wi-Fi	IEEE 802.11b/g/n/ax 2.4000~2.4835 GHz, 2.4G,≤20dBm
Wi-Fi Pairing	Bluetooth pairing
Storage	Micro SD card (support max. 256 GB)
Management Software	DMSS
Mobile Client	iOS;Android

## General

Certifications	CE
Power Supply	12 VDC
Power Consumption	Basic: 2.6 W Max.: 10.6 W (pulling stream+ IR + siren and light active deterrence)
Operating Temperature	−30 °C to +50 °C (−22 °F to +122 °F)
Operating Humidity	≤95% (RH), non-condensing
Protection	IP66
Casing Material	Plastic
Product Dimensions	159.4 mm × 119.1 mm × 210 mm (6.28" × 4.69" × 8.27") (L × W × H)
Net Weight	585 g (1.29 lb)

## What's in the box

